

Unidirectional banjo valves, pneumatic release, port 2 with female thread



Darba spiediens  
0.3 - 10 bar  
Regulēšanas spiediens  
0.5 - 2.5 bar, depending on operating pressure  
Vielas temperatūra  
max. 60 °C  
Uzstādīšanas stāvoklis  
Any. The ring piece must be positioned before the valve is tightened  
Materiāls  
Niķelēts misiņš  
Blīvējums  
Perbunan

## Apraksts

For stopping and positioning the cylinder movement: If a control signal is present at port 3 (see drawing), air can flow to and from the cylinder. If no control signal is present, the cylinder exhaust air is shut off by the unidirectional valve. &lt;br&gt;The cylinder is stopped. Releasable unidirectional valves are screwed directly onto the cylinder instead of the normal pipe connections.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Port 1	Port 2	Savienojums 3	B mm	C mm
K- 07 15 07 04	G 1/8"	G 1/8"	M5	38.0	21.5
K- 07 15 07 03	G 1/4"	G 1/4"	G 1/8"	43.0	25.4
K- 07 15 07 05	G 3/8"	G 3/8"	G 1/8"	46.0	31.6
K- 07 15 07 02	G 1/2"	G 1/2"	G 1/8"	52.0	32.0