

Unidirectional banjo valves, pneumatic release, port 2 with female thread



Darba spiediens
0.3 - 10 bar
Regulēšanas spiediens
0.5 - 2.5 bar, depending on operating pressure
Vielas temperatūra
max. 60 °C
Uzstādīšanas stāvoklis
Any. The ring piece must be positioned before the valve is tightened
Materiāls
Niķelēts misiņš
Blīvējums
Perbunan

Apraksts

For stopping and positioning the cylinder movement: If a control signal is present at port 3 (see drawing), air can flow to and from the cylinder. If no control signal is present, the cylinder exhaust air is shut off by the unidirectional valve.
The cylinder is stopped. Releasable unidirectional valves are screwed directly onto the cylinder instead of the normal pipe connections.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Port 1	Port 2	Savienojums 3	B mm	C mm
K- 07 15 07 04	G 1/8"	G 1/8"	M5	38.0	21.5
K- 07 15 07 03	G 1/4"	G 1/4"	G 1/8"	43.0	25.4
K- 07 15 07 05	G 3/8"	G 3/8"	G 1/8"	46.0	31.6
K- 07 15 07 02	G 1/2"	G 1/2"	G 1/8"	52.0	32.0