


K-MV G D 24 V DC

Normally closed, directly operated, 24 V DC (direct current)



Aizsardzības veids
IP65 (with connector socket fitted)
Elektriskais pieslēgums
ISO 4400. cable socket (Pg 11P)
Vielas temperatūra
max. +80 °C with Perbunan-seal; max. +130 °C with FKM-Seal
Vītnes apraksts
G-thread acc. to DIN EN ISO 228-1, Rp-thread acc. to ISO 7-1
Iekšējās daļas
Stainless steel
Korpuss, vārsta ligzda
Brass
Blīvējums
Perbunan (NBR) or FKM

Apraksts

Standard series, proven over many years, available in three different versions: Directly operated, Combined operation, Pilot-operated. For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	maks. darba spiediens bar	NW	Blīvēšanas materiāls	A mm	B mm	Konstrukcija
K- 07 30 23 08	G 1/8	5	03	NBR	75.0	30.0	1
K- 07 30 23 10	G 1/8	5	03	FKM	75.0	30.0	1
K- 07 30 23 09	G 1/4	4	03	NBR	75.0	40.0	2
K- 07 30 23 11	G 1/4	4	03	FKM	75.0	40.0	2