

# K-MV G Z 230 V, 50 - 60

## HZ

Normally closed, combined operation, 230 V, 50 to 60 Hz



Aizsardzības veids  
IP65 (with connector socket fitted)  
Elektriskais pieslēgums  
For connector socket Pg 9/Pg 11, acc. to ISO 4400  
Vielas temperatūra  
-10 °C to +90 °C (NBR); -10 °C bis +140 °C (FKM)  
Iekšējās daļas  
Stainless steel  
Korpuss, vārsta ligzda  
Brass  
Blīvējums  
Perbunan (NBR) or FKM

## Apraksts

Economy series available in three different versions: Directly operated, Combined operation, Pilot-operated. For all applications with compressed air, neutral gases or low-viscosity, neutral media.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	maks. darba spiediens bar	NW	Blīvēšanas materiāls	A mm	B mm	Konstrukcija
K- 07 30 22 94	G 3/8	14	11	NBR/PA	54.0	56.0	8
K- 07 30 22 95	G 1/2	14	16	NBR/PA	54.0	70.0	8
K- 07 30 22 96	G 3/4	14	16	NBR/PA	54.0	70.0	8
K- 07 30 22 97	G 1	14	25	NBR/PA	67.0	104.0	8
K- 07 30 22 98	G 1	16	25	NBR/PA	54.0	104.0	8