

K-MV 0 D 230 V, 50 - 60

HZ

Normally open, directly operated, 230 V, 50 to 60 Hz



Aizsardzības veids
IP65 (with connector socket fitted)
Elektriskais pieslēgums
For connector socket Pg 9/Pg 11, acc. to ISO 4400
Vielas temperatūra
-10 °C to +90 °C (NBR); -10 °C bis +140 °C (FKM)
Iekšējās daļas
Stainless steel
Korpuss, vārsta ligzda
Brass
Blīvējums
Perbunan (NBR) or FKM

Apraksts

Economy series available in three different versions: Directly operated, Combined operation, Pilot-operated. For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | maks. darba spiediens bar | NW | Blīvēšanas materiāls | A mm | B mm | Konstrukcija |
|----------------|--------|------------------------------|----|----------------------|---------|---------|--------------|
| K- 07 30 23 66 | G 1/8 | 20 | 02 | FKM | 54.0 | 40.0 | 2 |
| K- 07 30 23 67 | G 1/8 | 14 | 03 | FKM | 54.0 | 40.0 | 2 |
| K- 07 30 23 68 | G 1/4 | 10 | 03 | FKM | 54.0 | 40.0 | 2 |
| K- 07 30 23 69 | G 1/4 | 4 | 05 | FKM | 54.0 | 40.0 | 2 |