

# K-MV 0 D 24 V DC

Normally open, directly operated, 24 V DC (direct current)



Aizsardzības veids  
IP65 (with connector socket fitted)  
Elektriskais pieslēgums  
For connector socket Pg 9/Pg 11, acc. to ISO 4400  
Vielas temperatūra  
-10 °C to +90 °C (NBR); -10 °C bis +140 °C (FKM)  
Iekšējās daļas  
Stainless steel  
Korpuss, vārsta ligzda  
Brass  
Blīvējums  
Perbunan (NBR) or FKM

## Apraksts

Economy series available in three different versions: Directly operated, Combined operation, Pilot-operated. For all applications with compressed air, neutral gases or low-viscosity, neutral media.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	maks. darba spiediens bar	NW	Blīvēšanas materiāls	A mm	B mm	Konstrukcija
K- 07 30 23 87	G 1/8	20	02	FKM	54.0	40.0	2
K- 07 30 23 88	G 1/8	14	03	FKM	54.0	40.0	2
K- 07 30 23 89	G 1/4	10	03	FKM	54.0	40.0	2
K- 07 30 23 90	G 1/4	4	05	FKM	54.0	40.0	2