



Darba vides
Filtered, unlubricated compressed air
Spiediena diapazons
0 - 7 bar (NC) with silver plate at manual override
0 - 5 bar (NO) with black plate at manual override
Savienojums
In manifold base
Temperatūras diapazons
-5 °C to +45 °C
Atvēršanas/aizvēršanas laiks
10 - 12 ms (depending on pressure)
Spoles jauda
2.5 W
Materiāls
Plastmasa
Blīvējums
NBR, stainless steel

Apraksts

Directly controlled 3/2-way solenoid valves specially designed for pneumatic applications. These valves are provided with a flange for assembly on an individual base or multiple manifold base. They feature a monostable manual operator. The scope of supply includes two fixing bolts and a flange gasket. The coils can be turned 180°.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Spoles jauda W	Funkcija	Spriegums	Savienojums	H mm	B mm
K- 07 15 14 18	2.5	NC	24 V DC	Cable (30 cm)	42.0	15.0
K- 07 15 14 19	2.5	NC	24 V DC	for system plug	42.0	15.0
K- 07 15 14 20	2.5	NC	12 V DC	Cable (30 cm)	42.0	15.0
K- 07 15 14 21	2.5	NC	12 V DC	for system plug	42.0	15.0
K- 07 15 14 22	2.5	NO	24 V DC	Cable (30 cm)	42.0	15.0
K- 07 15 14 23	2.5	NO	24 V DC	for system plug	42.0	15.0
K- 07 15 14 24	2.5	NO	12 V DC	Cable (30 cm)	42.0	15.0
K- 07 15 14 25	2.5	NO	12 V DC	for system plug	42.0	15.0