



Darba vides  
Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Darba spiediens  
Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard)

Regulēšanas spiediens  
3 - 7 bar

Temperatūras diapazons  
-10 °C to +60 °C

Caurplūde  
200 NL/min (Ø 4), 500 NL/min (Ø 6), 800 NL/min (Ø 8)

Aizsardzības veids  
IP 65

Jaudas patēriņš  
0.6 W per pilot

Manuāla palīgvadība  
Latching (bistable), Monostable (non-latching) version also available on request

Vadību skaits  
Max. 16 (e.g. 16 spring return valves)

## Apraksts

These compact valve terminals, with a maximum flow rate of 800 NL/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Funkcija                     | Savienojums                 |
|----------------|------------------------------|-----------------------------|
| K- 07 15 22 49 | Standard, internal pilots    | Multi-pole                  |
| K- 07 15 22 48 | External pilots, dual supply | Multi-pole                  |
| K- 07 15 22 54 | Standard, internal pilots    | With integrated Profibus DP |
| K- 07 15 22 53 | External pilots              | With integrated Profibus DP |