

Electrical connection (multi-pole, 25-pin, IP 65)

**Darba vides**

Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Darba spiediens

Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard)

Regulēšanas spiediens

3 - 7 bar

Temperatūras diapazons

-10 °C to +60 °C

Aizsardzības veids

IP 65

Jaudas patēriņš

0.6 W per pilot

Manuāla palīgvadība

Latching (bistable), Monostable (non-latching) version also available on request

Vadību skaits

Max. 16 (e.g. 16 spring return valves)

Apraksts

These compact valve terminals, with a maximum flow rate of 800 Nl/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Definīcija
K- 07 15 22 45	IP 67 connector, 25-pin, with 1 m cable
K- 07 15 22 46	IP 67 connector, 25-pin, with 2.5 m cable
K- 07 15 22 47	IP 67 connector, 25-pin, with 5 m cable