



**Darba vides**  
Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

**Darba spiediens**  
Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard)

**Regulēšanas spiediens**  
3 - 7 bar

**Temperatūras diapazons**  
-10 °C to +60 °C

**Caurplūde**  
200 NL/min (Ø 4), 500 NL/min (Ø 6), 800 NL/min (Ø 8)

**Aizsardzības veids**  
IP 65

**Funkcija**  
Blind (terminates the system)

**Jaudas patēriņš**  
0.6 W per pilot

**Manuāla palīgvadība**  
Latching (bistable), Monostable (non-latching) version also available on request

**Vadību skaits**  
Max. 16 (e.g. 16 spring return valves)

## Apraksts

These compact valve terminals, with a maximum flow rate of 800 NL/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

### Apzīmējums

### Funkcija

K- 07 15 22 50 Blind (terminates the system)