



Darba spiediens  
OR-AND: 1.5-8 bar, NOT: 0.4-6 bar, YES - MEMORY: 0.0-8 bar (pilot pressure from 1.5-8 bar)  
Temperatūras diapazons  
-10 °C to +60 °C  
Savienojums  
Push-in fitting for 4 mm pipe  
Atiestatīšana  
OR - AND: by compressed air, MEMORY: by air, YES - NOT: by mechanical spring  
Caurpl\_de nom.  
100 l/min  
Nominālais Ø  
2.7 mm  
Materiāls  
Technopolymer  
Aizbīdnis  
Aluminium  
Blīvējums  
NBR

## Apraksts

Pneumatic logic elements are available with five different functions: OR, AND, NOT, YES, MEMORY. All elements have an adapter for the Q-rail (DIN EN 50022) integral with the body.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Nominālais Ø mm	Augstums mm	Funkcija	Garums mm
K- 07 15 13 77	2.7	40	OR	38.5
K- 07 15 13 78	2.7	40	AND	38.5
K- 07 15 13 79	2.7	40	NOT	55.2
K- 07 15 13 80	2.7	40	YES	55.2
K- 07 15 13 81	2.7	41	MEMORY	89.5