

# K-ZWEIHAND S VENTILE 0 GEH

Two-hand safety valve without housing



Darba vides  
Filtered, unlubricated compressed air  
Ekspluatācijas spiediens  
2.5 - 8 bar  
Temperatūras diapazons  
-10 °C to +60 °C  
Savienojums  
Push-in fitting for pipe 4 mm  
Caurpl\_de nom.  
85 l/min  
Darbība  
Pneumatic  
maks. ieejas signāla laika nobīde  
0.4

## Apraksts

This pushbutton panel according to EN574 Type III A is comprised of a dual manual control valve with a housing and manifold. The valve only generates an output signal if two synchronised input signals are received within < 0.4 sec. If one input signal is interrupted, the output signal is interrupted as well. An emergency stop valve with a mushroom pushbutton is included. The housing can be screwed to the wall in any position. The valve manifold can optionally be supplied without the housing and with a DIN bar adapter. Applications: Two-hand safety valve for start-of-cycle control on a pneumatically operated machine.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Definīcija	Savienojums
K- 07 15 26 09	Two-hand safety valve without housing	Push-in fitting for 4 mm pipe
K- 07 15 26 10	mounting element	-