

# K-WV 3/2 5/2 NAMUR

3/2 and 5/2-way spool valves

**HANSA FLEX**  
OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA



Darba vides  
Air, neutral gases, filtered  
Diferenciālais spiediens  
2 - 10 bar  
pieļaujamais statistiskais spiediens  
10 bar  
Eksploatācijas temperatūra  
-25 °C to +60 °C  
Elektriskais pieslēgums  
Connector socket Pg 9P, 3 x DIN 46244 / VDE 0580  
Korpuss  
Aluminium, anodised black  
Blīvējums  
NBR and PUR

## Apraksts

Pilot-operated 3/2 and 5/2-way spool valves with threaded port connections and a NAMUR style interface. The two conversion plates supplied with each valve allow the device to be adapted to a 3/2-way or 5/2-way function. The valve is turned on by a continuous signal. Turning off causes the piston to be returned to its initial position under pressure. Includes a manual operator as standard.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Spriegums	Port 1	Pieslēgums 3 + 5	Caurpl_de nom. l/min	DN
K- 07 15 00 01	230 V, 50 Hz	G 1/4"	G 1/8"	700	6
K- 07 15 00 02	24 V DC	G 1/4"	G 1/8"	700	6