

K-WV 3/2 5/2 NAMUR LB

3/2 and 5/2-way spool valves with NAMUR style interface



Darba vides
Air, neutral gases, filtered
Darba spiediens
1.5 - 8 bar
Eksploatācijas temperatūra
+5 °C to +50 °C
Elektriskais pieslēgums
Plug connector PG 9
Korpuss
Aluminium
Blīvējums
NBR

Apraksts

Pilot-operated 3/2 and 5/2-way spool valves with threaded ports and a NAMUR style interface. Combines high-quality design with a low price. By adding the conversion plate supplied with each valve, the device can be adapted to a 3/2-way function. The valve is turned on by a continuous signal. Turning off causes the piston to be returned to its initial position under pressure. Includes a manual operator as standard.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Spriegums	Port 1	Pieslēgums 3 + 5	Caurpl_de nom. l/min	DN
K- 07 15 00 09	230 V, 50 Hz	G 1/4"	G 1/4"	1370	8
K- 07 15 00 10	24 V DC	G 1/4"	G 1/4"	1370	8
K- 07 15 00 11	230 V, 50 Hz	G 3/8"	G 1/4"	1650	10
K- 07 15 00 12	24 V DC	G 3/8"	G 1/4"	1650	10