



Izmantošana  
for pressure relief valve HK VMP BL

## Produkts

Apzīmējums	piemērots vārstam ar T+P savienojumu	Spiediena iestatīšanas robežas, bar	H mm	Ø D mm	Svars kg
HK VMP BL 14 050	1/4"	5 - 50	25.1	8.6	0.01
HK VMP BL 14 220	1/4"	50 - 220	24.8	8.6	0.01
HK VMP BL 14 350	1/4" (tikai metāla korpuss)	180 - 350	25.0	8.7	0.01
HK VMP BL 38 040	3/8"	4 - 40	30.3	13.6	0.02
HK VMP BL 38 080	3/8"	20 - 80	33.0	13.4	0.02
HK VMP BL 38 220	3/8"	50 - 220	33.7	14.0	0.02
HK VMP BL 38 350	3/8" (tikai metāla korpuss)	180 - 350	35.8	14.3	0.02
HK VMP BL 12 040	1/2"	4 - 40	41.0	15.3	0.02
HK VMP BL 12 080	1/2"	20 - 80	42.2	14.8	0.02
HK VMP BL 12 220	1/2"	50 - 220	42.2	16.8	0.02
HK VMP BL 12 350	1/2" (tikai metāla korpuss)	180 - 350	41.7	16.2	0.02
HK VMP BL 34 20 040	3/4" un 1"	4 - 40	42.0	17.5	0.02
HK VMP BL 34 20 080	3/4" un 1"	20 - 80	45.5	16.9	0.02
HK VMP BL 34 20 220	3/4" un 1"	50 - 220	42.1	20.1	0.02
HK VMP BL 34 20 350	3/4" un 1" (tikai metāla korpuss)	180 - 350	45.1	20.5	0.02