



Materiāls
Tērauds S355J0 (Fe510C)

Norādīt

ØA pielāide: +0,2

Produkts

Apzīmējums	Ø A mm	Ø C mm	Ø D mm	B mm	G	Svars kg	SM
HK CFL 0035 072	35.0	60	72.0	10.00	4 x Ø 7	0.23	3 x 45°
HK CFL 0040 080	40.0	65	80.0	12.00	4 x Ø 9	0.33	3 x 45°
HK CFL 0042 089	42.0	70	89.0	12.00	4 x Ø 9	0.43	3 x 45°
HK CFL 0045 095	45.0	75	95.0	12.00	4 x Ø 9	0.50	3 x 45°
HK CFL 0050 109	50.0	87	109.0	12.50	4 x Ø 11	0.66	4 x 45°
HK CFL 0055 123	55.0	100	123.0	14.50	4 x Ø 11	1.00	4 x 45°
HK CFL 0060 128	60.0	105	128.0	14.50	4 x Ø 13	1.09	4 x 45°
HK CFL 0065 135	65.0	110	135.0	15.50	4 x Ø 13	1.30	4 x 45°
HK CFL 0070 142	70.0	117	142.0	16.50	4 x Ø 13	1.50	5 x 45°
HK CFL 0073 145	73.0	120	145.0	16.50	4 x Ø 13	1.50	5 x 45°
HK CFL 0075 152	75.0	125	152.0	16.50	4 x Ø 13	1.68	5 x 45°
HK CFL 0080 162	80.0	127	162.0	16.50	4 x Ø 15	1.94	5 x 45°
HK CFL 0090 175	90.0	145	175.0	18.50	4 x Ø 15	2.44	5 x 45°
HK CFL 0095 181	95.0	149	181.0	18.50	6 x Ø 17	2.53	7 x 45°
HK CFL 0100 188	100.0	155	188.0	18.50	6 x Ø 17	2.81	7 x 45°
HK CFL 0105 188	105.0	156	188.0	24.50	6 x Ø 17	3.44	8 x 45°
HK CFL 0115 194	115.0	162	194.0	24.50	6 x Ø 17	3.47	8 x 45°
HK CFL 0125 228	123.0	190	228.0	28.00	6 x Ø 21	5.95	8 x 45°
HK CFL 0140 240	138.0	200	240.0	28.00	6 x Ø 21	6.10	8 x 45°
HK CFL 0145 250	143.0	210	250.0	28.00	6 x Ø 21	6.65	8 x 45°
HK CFL 0160 280	158.0	230	280.0	33.00	6 x Ø 23	9.98	10 x 45°
HK CFL 0170 300	168.0	250	300.0	38.00	6 x Ø 25	13.30	12 x 45°
HK CFL 0180 325	178.0	270	325.0	38.00	6 x Ø 28	15.90	12 x 45°