

Galvenais korpuss dubultas darbības hidrauliskajam cilindram 200 bar



Materiāls
Tērauda lējums UNI 5007-G26

Produkts

| Apzīmējums | Ø A mm | Ø D mm | Ø S mm | F | L mm | L1 mm | Svars kg | piemērots blīvējumu komplekts |
|--------------|-----------|-----------|-----------|----------|---------|----------|-------------|-------------------------------|
| HK F 32 16 | 32 | 40 | 16 | M 36x1.5 | 40 | 32 | 1.0 | HK DSF 32 16 |
| HK F 40 28 | 40 | 50 | 28 | M 44x1.5 | 40 | 32 | 1.0 | HK DSF 40 28 |
| HK F 40 30 | 40 | 50 | 30 | M 44x1.5 | 40 | 32 | 1.0 | HK DSF 40 30 |
| HK F 45 20 | 45 | 55 | 20 | M 49x1.5 | 40 | 32 | 1.0 | HK DSF 45 20 |
| HK F 45 30 | 45 | 55 | 30 | M 49x1.5 | 40 | 32 | 1.0 | HK DSF 45 30 |
| HK F 50 28 | 50 | 60 | 28 | M 54x1.5 | 43 | 35 | 1.2 | HK DSF 50 28 |
| HK F 63 25 | 63 | 73 | 25 | M 68x1.5 | 50 | 40 | 1.3 | HK DSF 63 25 |
| HK F 6336 | 63 | 73 | 36 | M 68x1.5 | 50 | 40 | 1.2 | HK DSF 63 36 |
| HK F 63 45 | 63 | 73 | 45 | M 68x1.5 | 50 | 40 | 1.3 | HK DSF 63 45 |
| HK F 125 80 | 125 | 145 | 80 | M 130x2 | 92 | 80 | 5.0 | HK DSF 125 80 |
| HK F 140 100 | 140 | 160 | 100 | M 145x2 | 92 | 80 | 4.0 | HK DSF 140 100 |
| HK F 150 100 | 150 | 170 | 100 | M 155x2 | 102 | 90 | 4.5 | HK DSF 150 100 |