



Darba vides
Filtered (50 µm), unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Darba spiediens
1 to 8 bar

Temperatūras diapazons
-15 °C to +80 °C

Blīvējums
NBR for speeds up to 1 m/s
iekšēja/ārēja lente
Stainless steel

Korpuss
Jacket made from anodised aluminium alloy
Slīdes (virzuļa vadība)
Anodised aluminium alloy

Apraksts

These double-acting cylinders can also be supplied with strokes greater than 5 m, providing the stroke length is approximately equal to the overall length. They are equipped with magnets as standard for indicating the position as well as pneumatic, adjustable end position cushioning. Limit switches and hydraulic shock absorbers can be mounted as add-on modules.

Norādot

Further information on request

Produkts

| Apzīmējums | Spēks 6 bar N | Ø virzulim | Gājiens mm | Savienojums | maks. sānslodze |
|----------------|------------------|------------|---------------|-------------|-----------------|
| K- 07 15 07 34 | 110 | 16 mm | 100 | M5 | 0.3 Nm |
| K- 07 15 07 35 | 110 | 16 mm | 200 | M5 | 0.3 Nm |
| K- 07 15 07 36 | 110 | 16 mm | 300 | M5 | 0.3 Nm |
| K- 07 15 07 37 | 110 | 16 mm | 400 | M5 | 0.3 Nm |
| K- 07 15 07 38 | 110 | 16 mm | 500 | M5 | 0.3 Nm |
| K- 07 15 07 39 | 110 | 16 mm | 600 | M5 | 0.3 Nm |
| K- 07 15 07 40 | 110 | 16 mm | 700 | M5 | 0.3 Nm |
| K- 07 15 07 41 | 110 | 16 mm | 800 | M5 | 0.3 Nm |
| K- 07 15 07 42 | 110 | 16 mm | 900 | M5 | 0.3 Nm |
| K- 07 15 07 43 | 110 | 16 mm | 1000 | M5 | 0.3 Nm |
| K- 07 15 07 44 | 110 | 16 mm | 1200 | M5 | 0.3 Nm |
| K- 07 15 07 45 | 110 | 16 mm | 1400 | M5 | 0.3 Nm |
| K- 07 15 07 46 | 110 | 16 mm | 2000 | M5 | 0.3 Nm |
| K- 07 15 07 47 | 250 | 25 mm | 100 | G 1/8" | 1.0 Nm |
| K- 07 15 07 48 | 250 | 25 mm | 200 | G 1/8" | 1.0 Nm |
| K- 07 15 07 49 | 250 | 25 mm | 300 | G 1/8" | 1.0 Nm |
| K- 07 15 07 50 | 250 | 25 mm | 400 | G 1/8" | 1.0 Nm |
| K- 07 15 07 51 | 250 | 25 mm | 500 | G 1/8" | 1.0 Nm |
| K- 07 15 07 52 | 250 | 25 mm | 600 | G 1/8" | 1.0 Nm |
| K- 07 15 07 53 | 250 | 25 mm | 700 | G 1/8" | 1.0 Nm |
| K- 07 15 07 54 | 250 | 25 mm | 800 | G 1/8" | 1.0 Nm |
| K- 07 15 07 55 | 250 | 25 mm | 900 | G 1/8" | 1.0 Nm |
| K- 07 15 07 56 | 250 | 25 mm | 1000 | G 1/8" | 1.0 Nm |
| K- 07 15 07 57 | 250 | 25 mm | 1200 | G 1/8" | 1.0 Nm |
| K- 07 15 07 58 | 250 | 25 mm | 1400 | G 1/8" | 1.0 Nm |
| K- 07 15 07 59 | 250 | 25 mm | 2000 | G 1/8" | 1.0 Nm |
| K- 07 15 07 60 | 420 | 32 mm | 100 | G 1/4" | 2.0 Nm |
| K- 07 15 07 61 | 420 | 32 mm | 200 | G 1/4" | 2.0 Nm |
| K- 07 15 07 62 | 420 | 32 mm | 300 | G 1/4" | 2.0 Nm |
| K- 07 15 07 63 | 420 | 32 mm | 400 | G 1/4" | 2.0 Nm |
| K- 07 15 07 64 | 420 | 32 mm | 500 | G 1/4" | 2.0 Nm |
| K- 07 15 07 65 | 420 | 32 mm | 600 | G 1/4" | 2.0 Nm |

| Apzīmējums | Spēks 6 bar N | Ø virzulim | Gājiens mm | Savienojums | maks. sānslodze |
|----------------|------------------|------------|---------------|-------------|-----------------|
| K- 07 15 07 66 | 420 | 32 mm | 700 | G 1/4" | 2.0 Nm |
| K- 07 15 07 67 | 420 | 32 mm | 800 | G 1/4" | 2.0 Nm |
| K- 07 15 07 68 | 420 | 32 mm | 900 | G 1/4" | 2.0 Nm |
| K- 07 15 07 69 | 420 | 32 mm | 1000 | G 1/4" | 2.0 Nm |
| K- 07 15 07 70 | 420 | 32 mm | 1200 | G 1/4" | 2.0 Nm |
| K- 07 15 07 71 | 420 | 32 mm | 1400 | G 1/4" | 2.0 Nm |
| K- 07 15 07 72 | 420 | 32 mm | 2000 | G 1/4" | 2.0 Nm |
| K- 07 15 07 73 | 640 | 40 mm | 100 | G 1/4" | 4.0 Nm |
| K- 07 15 07 74 | 640 | 40 mm | 200 | G 1/4" | 4.0 Nm |
| K- 07 15 07 75 | 640 | 40 mm | 300 | G 1/4" | 4.0 Nm |
| K- 07 15 07 76 | 640 | 40 mm | 400 | G 1/4" | 4.0 Nm |
| K- 07 15 07 77 | 640 | 40 mm | 500 | G 1/4" | 4.0 Nm |
| K- 07 15 07 78 | 640 | 40 mm | 600 | G 1/4" | 4.0 Nm |
| K- 07 15 07 79 | 640 | 40 mm | 700 | G 1/4" | 4.0 Nm |
| K- 07 15 07 80 | 640 | 40 mm | 800 | G 1/4" | 4.0 Nm |
| K- 07 15 07 81 | 640 | 40 mm | 900 | G 1/4" | 4.0 Nm |
| K- 07 15 07 82 | 640 | 40 mm | 1000 | G 1/4" | 4.0 Nm |
| K- 07 15 07 83 | 640 | 40 mm | 1200 | G 1/4" | 4.0 Nm |
| K- 07 15 07 84 | 640 | 40 mm | 1400 | G 1/4" | 4.0 Nm |
| K- 07 15 07 85 | 640 | 40 mm | 2000 | G 1/4" | 4.0 Nm |
| K- 07 15 07 86 | 1550 | 63 mm | 100 | G 3/8" | 8.0 Nm |
| K- 07 15 07 87 | 1550 | 63 mm | 200 | G 3/8" | 8.0 Nm |
| K- 07 15 07 88 | 1550 | 63 mm | 300 | G 3/8" | 8.0 Nm |
| K- 07 15 07 89 | 1550 | 63 mm | 400 | G 3/8" | 8.0 Nm |
| K- 07 15 07 90 | 1550 | 63 mm | 500 | G 3/8" | 8.0 Nm |
| K- 07 15 07 91 | 1550 | 63 mm | 600 | G 3/8" | 8.0 Nm |
| K- 07 15 07 92 | 1550 | 63 mm | 700 | G 3/8" | 8.0 Nm |
| K- 07 15 07 93 | 1550 | 63 mm | 800 | G 3/8" | 8.0 Nm |
| K- 07 15 07 94 | 1550 | 63 mm | 900 | G 3/8" | 8.0 Nm |
| K- 07 15 07 95 | 1550 | 63 mm | 1000 | G 3/8" | 8.0 Nm |
| K- 07 15 07 96 | 1550 | 63 mm | 1200 | G 3/8" | 8.0 Nm |
| K- 07 15 07 97 | 1550 | 63 mm | 1400 | G 3/8" | 8.0 Nm |
| K- 07 15 07 98 | 1550 | 63 mm | 2000 | G 3/8" | 8.0 Nm |