



Darba vides

Filtered (50 µm), unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Darba spiediens

1 to 8 bar

Temperatūras diapazons

-15 °C to +80 °C

Blīvējums

NBR for speeds up to 1 m/s

iekšēja/ārēja lente

Stainless steel

Korpuss

Jacket made from anodised aluminium alloy

Slīdes (virzuļa vadība)

Anodised aluminium alloy

Apraksts

These double-acting cylinders can also be supplied with strokes greater than 5 m, providing the stroke length is approximately equal to the overall length. They are equipped with magnets as standard for indicating the position as well as pneumatic, adjustable end position cushioning. Limit switches and hydraulic shock absorbers can be mounted as add-on modules.

Norādīt

Further information on request

Produkts

Apzīmējums	Spēks 6 bar N	Ø virzulim	Gājiens mm	Savienojums	maks. sānslodze
K- 07 15 07 34	110	16 mm	100	M5	0.3 Nm
K- 07 15 07 35	110	16 mm	200	M5	0.3 Nm
K- 07 15 07 36	110	16 mm	300	M5	0.3 Nm
K- 07 15 07 37	110	16 mm	400	M5	0.3 Nm
K- 07 15 07 38	110	16 mm	500	M5	0.3 Nm
K- 07 15 07 39	110	16 mm	600	M5	0.3 Nm
K- 07 15 07 40	110	16 mm	700	M5	0.3 Nm
K- 07 15 07 41	110	16 mm	800	M5	0.3 Nm
K- 07 15 07 42	110	16 mm	900	M5	0.3 Nm
K- 07 15 07 43	110	16 mm	1000	M5	0.3 Nm
K- 07 15 07 44	110	16 mm	1200	M5	0.3 Nm
K- 07 15 07 45	110	16 mm	1400	M5	0.3 Nm
K- 07 15 07 46	110	16 mm	2000	M5	0.3 Nm
K- 07 15 07 47	250	25 mm	100	G 1/8"	1.0 Nm
K- 07 15 07 48	250	25 mm	200	G 1/8"	1.0 Nm
K- 07 15 07 49	250	25 mm	300	G 1/8"	1.0 Nm
K- 07 15 07 50	250	25 mm	400	G 1/8"	1.0 Nm
K- 07 15 07 51	250	25 mm	500	G 1/8"	1.0 Nm
K- 07 15 07 52	250	25 mm	600	G 1/8"	1.0 Nm
K- 07 15 07 53	250	25 mm	700	G 1/8"	1.0 Nm
K- 07 15 07 54	250	25 mm	800	G 1/8"	1.0 Nm
K- 07 15 07 55	250	25 mm	900	G 1/8"	1.0 Nm
K- 07 15 07 56	250	25 mm	1000	G 1/8"	1.0 Nm
K- 07 15 07 57	250	25 mm	1200	G 1/8"	1.0 Nm
K- 07 15 07 58	250	25 mm	1400	G 1/8"	1.0 Nm
K- 07 15 07 59	250	25 mm	2000	G 1/8"	1.0 Nm
K- 07 15 07 60	420	32 mm	100	G 1/4"	2.0 Nm
K- 07 15 07 61	420	32 mm	200	G 1/4"	2.0 Nm
K- 07 15 07 62	420	32 mm	300	G 1/4"	2.0 Nm
K- 07 15 07 63	420	32 mm	400	G 1/4"	2.0 Nm
K- 07 15 07 64	420	32 mm	500	G 1/4"	2.0 Nm
K- 07 15 07 65	420	32 mm	600	G 1/4"	2.0 Nm

Apzīmējums	Spēks 6 bar N	Ø virzulim	Gājiens mm	Savienojums	maks. sānslodze
K- 07 15 07 66	420	32 mm	700	G 1/4"	2.0 Nm
K- 07 15 07 67	420	32 mm	800	G 1/4"	2.0 Nm
K- 07 15 07 68	420	32 mm	900	G 1/4"	2.0 Nm
K- 07 15 07 69	420	32 mm	1000	G 1/4"	2.0 Nm
K- 07 15 07 70	420	32 mm	1200	G 1/4"	2.0 Nm
K- 07 15 07 71	420	32 mm	1400	G 1/4"	2.0 Nm
K- 07 15 07 72	420	32 mm	2000	G 1/4"	2.0 Nm
K- 07 15 07 73	640	40 mm	100	G 1/4"	4.0 Nm
K- 07 15 07 74	640	40 mm	200	G 1/4"	4.0 Nm
K- 07 15 07 75	640	40 mm	300	G 1/4"	4.0 Nm
K- 07 15 07 76	640	40 mm	400	G 1/4"	4.0 Nm
K- 07 15 07 77	640	40 mm	500	G 1/4"	4.0 Nm
K- 07 15 07 78	640	40 mm	600	G 1/4"	4.0 Nm
K- 07 15 07 79	640	40 mm	700	G 1/4"	4.0 Nm
K- 07 15 07 80	640	40 mm	800	G 1/4"	4.0 Nm
K- 07 15 07 81	640	40 mm	900	G 1/4"	4.0 Nm
K- 07 15 07 82	640	40 mm	1000	G 1/4"	4.0 Nm
K- 07 15 07 83	640	40 mm	1200	G 1/4"	4.0 Nm
K- 07 15 07 84	640	40 mm	1400	G 1/4"	4.0 Nm
K- 07 15 07 85	640	40 mm	2000	G 1/4"	4.0 Nm
K- 07 15 07 86	1550	63 mm	100	G 3/8"	8.0 Nm
K- 07 15 07 87	1550	63 mm	200	G 3/8"	8.0 Nm
K- 07 15 07 88	1550	63 mm	300	G 3/8"	8.0 Nm
K- 07 15 07 89	1550	63 mm	400	G 3/8"	8.0 Nm
K- 07 15 07 90	1550	63 mm	500	G 3/8"	8.0 Nm
K- 07 15 07 91	1550	63 mm	600	G 3/8"	8.0 Nm
K- 07 15 07 92	1550	63 mm	700	G 3/8"	8.0 Nm
K- 07 15 07 93	1550	63 mm	800	G 3/8"	8.0 Nm
K- 07 15 07 94	1550	63 mm	900	G 3/8"	8.0 Nm
K- 07 15 07 95	1550	63 mm	1000	G 3/8"	8.0 Nm
K- 07 15 07 96	1550	63 mm	1200	G 3/8"	8.0 Nm
K- 07 15 07 97	1550	63 mm	1400	G 3/8"	8.0 Nm
K- 07 15 07 98	1550	63 mm	2000	G 3/8"	8.0 Nm