

K-KURZH ZYL EINFACHW

Short-stroke cylinders, single-acting (magnetic)



Darba vides

Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Eksploatācijas spiediens

maks. 10 bar

Temperatūras diapazons

-10 °C to +80 °C

Sākuma spiediens

0,6 bar (Ø 12 bis Ø 32), 0,4 bar (Ø 40 bis Ø 80)

Virzuļkāts

Stahl C45, hartverchromt

Caurule

Aluminium alloy, anodised

Virzulis

Ø 12 to Ø 63 synthetic (acetal) resin, Ø 80 alu/PTFE

Blīvējums

NBR

Galvas diametrs

Ø 12 to Ø 25 painted brass, Ø 32 to Ø 80 aluminium

Apraksts

Suitable for installation in limited spaces, with magnet.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Ø virzulim | Gājiens mm | Savienojums | Virzuļkāta iekšējā vītne |
|----------------|------------|---------------|-------------|--------------------------|
| K- 07 15 11 87 | 12 mm | 10 | M5 | M 3 |
| K- 07 15 11 88 | 12 mm | 25 | M5 | M 3 |
| K- 07 15 11 89 | 16 mm | 10 | M5 | M 5 |
| K- 07 15 11 90 | 16 mm | 25 | M5 | M 5 |
| K- 07 15 11 91 | 20 mm | 10 | M5 | M 5 |
| K- 07 15 11 92 | 20 mm | 25 | M5 | M 5 |
| K- 07 15 11 93 | 25 mm | 10 | G 1/8" | M 5 |
| K- 07 15 11 94 | 25 mm | 25 | G 1/8" | M 5 |
| K- 07 15 11 95 | 32 mm | 10 | G 1/8" | M 6 |
| K- 07 15 11 96 | 32 mm | 25 | G 1/8" | M 6 |
| K- 07 15 11 97 | 40 mm | 10 | G 1/8" | M 6 |
| K- 07 15 11 98 | 40 mm | 25 | G 1/8" | M 6 |
| K- 07 15 11 99 | 50 mm | 25 | G 1/8" | M 8 |
| K- 07 15 12 00 | 63 mm | 25 | G 1/8" | M 8 |