

# K-KURZH ZYL EINFACHW

Short-stroke cylinders, single-acting (magnetic)



## Darba vides

Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Eksploatācijas spiediens

maks. 10 bar

Temperatūras diapazons

-10 °C to +80 °C

Sākuma spiediens

0,6 bar (Ø 12 bis Ø 32), 0,4 bar (Ø 40 bis Ø 80)

Virzuļkāts

Stahl C45, hartverchromt

Caurule

Aluminium alloy, anodised

Virzulis

Ø 12 to Ø 63 synthetic (acetal) resin, Ø 80 alu/PTFE

Blīvējums

NBR

Galvas diametrs

Ø 12 to Ø 25 painted brass, Ø 32 to Ø 80 aluminium

## Apraksts

Suitable for installation in limited spaces, with magnet.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Ø virzulim	Gājiens mm	Savienojums	Virzuļkāta iekšējā vītne
K- 07 15 11 87	12 mm	10	M5	M 3
K- 07 15 11 88	12 mm	25	M5	M 3
K- 07 15 11 89	16 mm	10	M5	M 5
K- 07 15 11 90	16 mm	25	M5	M 5
K- 07 15 11 91	20 mm	10	M5	M 5
K- 07 15 11 92	20 mm	25	M5	M 5
K- 07 15 11 93	25 mm	10	G 1/8"	M 5
K- 07 15 11 94	25 mm	25	G 1/8"	M 5
K- 07 15 11 95	32 mm	10	G 1/8"	M 6
K- 07 15 11 96	32 mm	25	G 1/8"	M 6
K- 07 15 11 97	40 mm	10	G 1/8"	M 6
K- 07 15 11 98	40 mm	25	G 1/8"	M 6
K- 07 15 11 99	50 mm	25	G 1/8"	M 8
K- 07 15 12 00	63 mm	25	G 1/8"	M 8