

K-KURZH ZYL EINFACHW SER ASQ

HANSA FLEX

OFICIĀLĀ LATVIJAS PĀRSTĀVniecība

Short-stroke cylinders, single-acting (pressureless in the retracted position), with magnet, non-cushioned, with female thread, »ASQ« Series



Darba vides
Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Darba spiediens
1 - 10 bar (double-acting); 2 - 10 bar (single-acting)

Temperatūras diapazons
-20 °C to +80 °C

Virzuļkāts
gehärteter Stahl, hartverchromt

Virzulis
Brass (12 to 16 mm); Aluminium (20 to 100 mm)

Blīvējums
NBR

Cilindra caurule
Aluminium

Apraksts

Specially for use where space is in short supply. Version with magnetic piston. Short-stroke cylinder in two different versions: Series "ACQ", double-acting, Ø 12 - 100

Series "ASQ", single-acting, Ø 12 - 63

Produkts

| Apzīmējums | Ø virzulim | Gājiens mm | Konstrukcija | Ø virzuļkātam mm | Virzuļkāta iekšējā vītne |
|----------------|------------|---------------|--------------|---------------------|--------------------------|
| K- 07 15 13 33 | 12 mm | 5 | 4 | 6 | M 3 x 0.5 |
| K- 07 15 13 34 | 12 mm | 10 | 4 | 6 | M 3 x 0.5 |
| K- 07 15 13 35 | 12 mm | 15 | 4 | 6 | M 3 x 0.5 |
| K- 07 15 13 36 | 12 mm | 20 | 4 | 6 | M 3 x 0.5 |
| K- 07 15 13 37 | 16 mm | 5 | 4 | 8 | M 4 x 0.7 |
| K- 07 15 13 38 | 16 mm | 10 | 4 | 8 | M 4 x 0.7 |
| K- 07 15 13 39 | 16 mm | 15 | 4 | 8 | M 4 x 0.7 |
| K- 07 15 13 40 | 16 mm | 20 | 4 | 8 | M 4 x 0.7 |
| K- 07 15 13 41 | 20 mm | 5 | 5 | 10 | M 5 x 0.8 |
| K- 07 15 13 42 | 20 mm | 10 | 5 | 10 | M 5 x 0.8 |
| K- 07 15 13 43 | 20 mm | 15 | 5 | 10 | M 5 x 0.8 |
| K- 07 15 13 44 | 20 mm | 20 | 5 | 10 | M 5 x 0.8 |
| K- 07 15 13 45 | 20 mm | 25 | 5 | 10 | M 5 x 0.8 |
| K- 07 15 13 46 | 20 mm | 30 | 5 | 10 | M 5 x 0.8 |
| K- 07 15 13 47 | 25 mm | 5 | 5 | 12 | M 6 x 1 |
| K- 07 15 13 48 | 25 mm | 10 | 5 | 12 | M 6 x 1 |
| K- 07 15 13 49 | 25 mm | 15 | 5 | 12 | M 6 x 1 |
| K- 07 15 13 50 | 25 mm | 20 | 5 | 12 | M 6 x 1 |
| K- 07 15 13 51 | 25 mm | 25 | 5 | 12 | M 6 x 1 |
| K- 07 15 13 52 | 25 mm | 30 | 5 | 12 | M 6 x 1 |
| K- 07 15 13 53 | 32 mm | 5 | 6 | 16 | M 8 x 1.25 |
| K- 07 15 13 54 | 32 mm | 10 | 6 | 16 | M 8 x 1.25 |
| K- 07 15 13 55 | 32 mm | 15 | 6 | 16 | M 8 x 1.25 |
| K- 07 15 13 56 | 32 mm | 20 | 6 | 16 | M 8 x 1.25 |
| K- 07 15 13 57 | 32 mm | 25 | 6 | 16 | M 8 x 1.25 |
| K- 07 15 13 58 | 32 mm | 30 | 6 | 16 | M 8 x 1.25 |
| K- 07 15 13 59 | 40 mm | 5 | 6 | 16 | M 8 x 1.25 |
| K- 07 15 13 60 | 40 mm | 10 | 6 | 16 | M 8 x 1.25 |
| K- 07 15 13 61 | 40 mm | 15 | 6 | 16 | M 8 x 1.25 |
| K- 07 15 13 62 | 40 mm | 20 | 6 | 16 | M 8 x 1.25 |
| K- 07 15 13 63 | 40 mm | 25 | 6 | 16 | M 8 x 1.25 |
| K- 07 15 13 64 | 40 mm | 30 | 6 | 16 | M 8 x 1.25 |
| K- 07 15 13 65 | 50 mm | 5 | 6 | 20 | M 10 x 1.5 |
| K- 07 15 13 66 | 50 mm | 10 | 6 | 20 | M 10 x 1.5 |

| Apzīmējums | Ø virzulim | Gājiens mm | Konstrukcija | Ø virzuļkātām mm | Virzuļkāta iekšējā vītne |
|----------------|------------|---------------|--------------|---------------------|--------------------------|
| K- 07 15 13 67 | 50 mm | 15 | 6 | 20 | M 10 x 1.5 |
| K- 07 15 13 68 | 50 mm | 20 | 6 | 20 | M 10 x 1.5 |
| K- 07 15 13 69 | 50 mm | 25 | 6 | 20 | M 10 x 1.5 |
| K- 07 15 13 70 | 50 mm | 30 | 6 | 20 | M 10 x 1.5 |
| K- 07 15 13 71 | 63 mm | 5 | 6 | 20 | M 10 x 1.5 |
| K- 07 15 13 72 | 63 mm | 10 | 6 | 20 | M 10 x 1.5 |
| K- 07 15 13 73 | 63 mm | 15 | 6 | 20 | M 10 x 1.5 |
| K- 07 15 13 74 | 63 mm | 20 | 6 | 20 | M 10 x 1.5 |
| K- 07 15 13 75 | 63 mm | 25 | 6 | 20 | M 10 x 1.5 |
| K- 07 15 13 76 | 63 mm | 30 | 6 | 20 | M 10 x 1.5 |