

Darba vides

Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Darba spiediens

Max. 10 bar

Temperatūras diapazons

-20 °C to +70 °C (Ø 32 to Ø 63)

-10 °C to +70 °C (Ø 80 to Ø 125)

Sākuma spiediens

0,4 bar (Ø 32 bis Ø 40), 0,3 bar (Ø 50 bis Ø 63), 0,2 bar (Ø 80 bis Ø 125)

Virzuļkāts

Stahl C45, hartverchromt

Caurule

Anodised aluminium jacket with integrated T-slots

Uzstādīšana

Heads / jacket with self-tapping screws

Virzulis

POM (Ø 20 to Ø 63); Aluminium (Ø 80 to Ø 125)

Blīvējums

NBR



Apraksts

These cylinders are ideal for a wide range of applications owing to their robust design and excellent value for money. The standard type has a double-acting cylinder and features a magnetic piston as well as integrated cushioning. The magnetic switches can be mounted in two T-slots on the same side as the compressed air supply.
Cylinders of the same type can also be supplied on request with fixing parts for magnetic switches on three sides.
The version with a 125 mm bore is provided with fixing accessories on three sides as standard.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Ø virzulim	Gājiens mm	Savienojums	Ø virzuļkātam mm	Virzuļkāta ārējā vītne
K- 07 15 15 90	32 mm	25	G 1/8"	12	M 10 x 1.25
K- 07 15 15 91	32 mm	50	G 1/8"	12	M 10 x 1.25
K- 07 15 15 92	32 mm	80	G 1/8"	12	M 10 x 1.25
K- 07 15 15 93	32 mm	100	G 1/8"	12	M 10 x 1.25
K- 07 15 15 94	32 mm	125	G 1/8"	12	M 10 x 1.25
K- 07 15 15 95	32 mm	160	G 1/8"	12	M 10 x 1.25
K- 07 15 15 96	32 mm	200	G 1/8"	12	M 10 x 1.25
K- 07 15 15 97	32 mm	250	G 1/8"	12	M 10 x 1.25
K- 07 15 15 98	32 mm	320	G 1/8"	12	M 10 x 1.25
K- 07 15 15 99	32 mm	400	G 1/8"	12	M 10 x 1.25
K- 07 15 16 00	32 mm	500	G 1/8"	12	M 10 x 1.25
K- 07 15 16 01	32 mm	600	G 1/8"	12	M 10 x 1.25
K- 07 15 16 02	32 mm	800	G 1/8"	12	M 10 x 1.25
K- 07 15 16 03	40 mm	25	G 1/4"	16	M 12 x 1.25
K- 07 15 16 04	40 mm	50	G 1/4"	16	M 12 x 1.25
K- 07 15 16 05	40 mm	80	G 1/4"	16	M 12 x 1.25
K- 07 15 16 06	40 mm	100	G 1/4"	16	M 12 x 1.25
K- 07 15 16 07	40 mm	125	G 1/4"	16	M 12 x 1.25
K- 07 15 16 08	40 mm	160	G 1/4"	16	M 12 x 1.25
K- 07 15 16 09	40 mm	200	G 1/4"	16	M 12 x 1.25
K- 07 15 16 10	40 mm	250	G 1/4"	16	M 12 x 1.25
K- 07 15 16 11	40 mm	320	G 1/4"	16	M 12 x 1.25
K- 07 15 16 12	40 mm	400	G 1/4"	16	M 12 x 1.25
K- 07 15 16 13	40 mm	500	G 1/4"	16	M 12 x 1.25
K- 07 15 16 14	40 mm	600	G 1/4"	16	M 12 x 1.25
K- 07 15 16 15	40 mm	800	G 1/4"	16	M 12 x 1.25
K- 07 15 16 16	50 mm	25	G 1/4"	20	M 16 x 1.5
K- 07 15 16 17	50 mm	50	G 1/4"	20	M 16 x 1.5

Apzīmējums	Ø virzulim	Gājiens mm	Savienojums	Ø virzuļkātam mm	Virzuļkāta ārējā vītne
K- 07 15 16 18	50 mm	80	G 1/4"	20	M 16 x 1.5
K- 07 15 16 19	50 mm	100	G 1/4"	20	M 16 x 1.5
K- 07 15 16 20	50 mm	125	G 1/4"	20	M 16 x 1.5
K- 07 15 16 21	50 mm	160	G 1/4"	20	M 16 x 1.5
K- 07 15 16 22	50 mm	200	G 1/4"	20	M 16 x 1.5
K- 07 15 16 23	50 mm	250	G 1/4"	20	M 16 x 1.5
K- 07 15 16 24	50 mm	320	G 1/4"	20	M 16 x 1.5
K- 07 15 16 25	50 mm	400	G 1/4"	20	M 16 x 1.5
K- 07 15 16 26	50 mm	500	G 1/4"	20	M 16 x 1.5
K- 07 15 16 27	50 mm	600	G 1/4"	20	M 16 x 1.5
K- 07 15 16 28	50 mm	800	G 1/4"	20	M 16 x 1.5
K- 07 15 16 29	63 mm	25	G 3/8"	20	M 16 x 1.5
K- 07 15 16 30	63 mm	50	G 3/8"	20	M 16 x 1.5
K- 07 15 16 31	63 mm	80	G 3/8"	20	M 16 x 1.5
K- 07 15 16 32	63 mm	100	G 3/8"	20	M 16 x 1.5
K- 07 15 16 33	63 mm	125	G 3/8"	20	M 16 x 1.5
K- 07 15 16 34	63 mm	160	G 3/8"	20	M 16 x 1.5
K- 07 15 16 35	63 mm	200	G 3/8"	20	M 16 x 1.5
K- 07 15 16 36	63 mm	250	G 3/8"	20	M 16 x 1.5
K- 07 15 16 37	63 mm	320	G 3/8"	20	M 16 x 1.5
K- 07 15 16 38	63 mm	400	G 3/8"	20	M 16 x 1.5
K- 07 15 16 39	63 mm	500	G 3/8"	20	M 16 x 1.5
K- 07 15 16 40	63 mm	600	G 3/8"	20	M 16 x 1.5
K- 07 15 16 41	63 mm	800	G 3/8"	20	M 16 x 1.5
K- 07 15 16 42	80 mm	25	G 3/8"	25	M 20 x 1.5
K- 07 15 16 43	80 mm	50	G 3/8"	25	M 20 x 1.5
K- 07 15 16 44	80 mm	80	G 3/8"	25	M 20 x 1.5
K- 07 15 16 45	80 mm	100	G 3/8"	25	M 20 x 1.5
K- 07 15 16 46	80 mm	125	G 3/8"	25	M 20 x 1.5
K- 07 15 16 47	80 mm	160	G 3/8"	25	M 20 x 1.5
K- 07 15 16 48	80 mm	200	G 3/8"	25	M 20 x 1.5
K- 07 15 16 49	80 mm	250	G 3/8"	25	M 20 x 1.5
K- 07 15 16 50	80 mm	320	G 3/8"	25	M 20 x 1.5
K- 07 15 16 51	80 mm	400	G 3/8"	25	M 20 x 1.5
K- 07 15 16 52	80 mm	500	G 3/8"	25	M 20 x 1.5
K- 07 15 16 53	80 mm	600	G 3/8"	25	M 20 x 1.5
K- 07 15 16 54	80 mm	800	G 3/8"	25	M 20 x 1.5
K- 07 15 15 64	100 mm	25	G 1/2"	25	M 20 x 1.5
K- 07 15 15 65	100 mm	50	G 1/2"	25	M 20 x 1.5
K- 07 15 15 66	100 mm	80	G 1/2"	25	M 20 x 1.5
K- 07 15 15 67	100 mm	100	G 1/2"	25	M 20 x 1.5
K- 07 15 15 68	100 mm	125	G 1/2"	25	M 20 x 1.5
K- 07 15 15 69	100 mm	160	G 1/2"	25	M 20 x 1.5
K- 07 15 15 70	100 mm	200	G 1/2"	25	M 20 x 1.5
K- 07 15 15 71	100 mm	250	G 1/2"	25	M 20 x 1.5
K- 07 15 15 72	100 mm	320	G 1/2"	25	M 20 x 1.5
K- 07 15 15 73	100 mm	400	G 1/2"	25	M 20 x 1.5
K- 07 15 15 74	100 mm	500	G 1/2"	25	M 20 x 1.5
K- 07 15 15 75	100 mm	600	G 1/2"	25	M 20 x 1.5
K- 07 15 15 76	100 mm	800	G 1/2"	25	M 20 x 1.5
K- 07 15 15 77	125 mm	25	G 1/2"	32	M 27 x 2
K- 07 15 15 78	125 mm	50	G 1/2"	32	M 27 x 2
K- 07 15 15 79	125 mm	80	G 1/2"	32	M 27 x 2
K- 07 15 15 80	125 mm	100	G 1/2"	32	M 27 x 2
K- 07 15 15 81	125 mm	125	G 1/2"	32	M 27 x 2
K- 07 15 15 82	125 mm	160	G 1/2"	32	M 27 x 2
K- 07 15 15 83	125 mm	200	G 1/2"	32	M 27 x 2
K- 07 15 15 84	125 mm	250	G 1/2"	32	M 27 x 2

Apzīmējums	Ø virzulim	Gājiens mm	Savienojums	Ø virzuļkātām mm	Virzuļkāta ārējā vītne
K- 07 15 15 85	125 mm	320	G 1/2"	32	M 27 x 2
K- 07 15 15 86	125 mm	400	G 1/2"	32	M 27 x 2
K- 07 15 15 87	125 mm	500	G 1/2"	32	M 27 x 2
K- 07 15 15 88	125 mm	600	G 1/2"	32	M 27 x 2
K- 07 15 15 89	125 mm	800	G 1/2"	32	M 27 x 2