

K-RUNDZYLINDER DOPP M D

Rundzylinder, doppelwirkend (mit Magnet, mit einstellbarer Dämpfung)



Darba vides
Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Darba spiediens
Max. 10 bar

Temperatūras diapazons
-10 °C to +80 °C

Sākuma spiediens
0,8 bar (Ø 8 bis Ø 12), 0,6 bar (Ø 16 bis Ø 25)

Virzuļkāts
Stahl C45, hartverchromt

Caurule
Stainless steel 1.4301

Uzstādīšana
Flanged joint between stainless steel barrel and heads

Virzulis
Synthetic (acetal) resin

Blīvējums
NBR

Apraksts

Single and double-acting cylinders, with magnetic piston.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Ø virzulim	Gājiens mm	Savienojums	Virzuļkāta vītne
K- 07 15 24 89	16 mm	10	M5	M 6
K- 07 15 24 90	16 mm	25	M5	M 6
K- 07 15 24 91	16 mm	50	M5	M 6
K- 07 15 24 92	16 mm	80	M5	M 6
K- 07 15 24 93	16 mm	100	M5	M 6
K- 07 15 24 94	16 mm	125	M5	M 6
k- 07 15 24 95	16 mm	160	M5	M 6
K- 07 15 24 96	16 mm	200	M5	M 6
K- 07 15 24 97	20 mm	10	G 1/8"	M 8
K- 07 15 24 98	20 mm	25	G 1/8"	M 8
K- 07 15 24 99	20 mm	50	G 1/8"	M 8
K- 07 15 25 00	20 mm	80	G 1/8"	M 8
K- 07 15 25 01	20 mm	100	G 1/8"	M 8
K- 07 15 25 02	20 mm	125	G 1/8"	M 8
K- 07 15 25 03	20 mm	160	G 1/8"	M 8
K- 07 15 25 04	20 mm	200	G 1/8"	M 8
K- 07 15 25 05	20 mm	250	G 1/8"	M 8
K- 07 15 25 06	25 mm	10	G 1/8"	M 10 x 1.25
K- 07 15 25 07	25 mm	25	G 1/8"	M 10 x 1.25
K- 07 15 24 88	25 mm	50	G 1/8"	M 10 x 1.25
K- 07 15 25 08	25 mm	80	G 1/8"	M 10 x 1.25
K- 07 15 25 09	25 mm	100	G 1/8"	M 10 x 1.25
K- 07 15 25 10	25 mm	125	G 1/8"	M 10 x 1.25
K- 07 15 25 11	25 mm	160	G 1/8"	M 10 x 1.25
K- 07 15 25 12	25 mm	200	G 1/8"	M 10 x 1.25
K- 07 15 25 13	25 mm	250	G 1/8"	M 10 x 1.25