

# K-RUNDZYLINDER EINF 0 D

Miniature cylinders, single-acting (magnetic, non-cushioned)



Darba vides

Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Darba spiediens

Max. 10 bar

Temperatūras diapazons

-10 °C to +80 °C

Sākuma spiediens

0,8 bar (Ø 8 bis Ø 12), 0,6 bar (Ø 16 bis Ø 25)

Virzuļkāts

Stahl C45, hartverchromt

Caurule

Stainless steel 1.4301

Uzstādīšana

Flanged joint between stainless steel barrel and heads

Virzulis

Synthetic (acetal) resin

Blīvējums

NBR

## Apraksts

Single and double-acting cylinders, with magnetic piston.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Ø virzulim	Gājiens mm	Savienojums	Virzuļkāta vītne
K- 07 15 17 11	8 mm	10	M5	M 4
K- 07 15 17 12	8 mm	25	M5	M 4
K- 07 15 17 13	8 mm	50	M5	M 4
K- 07 15 17 14	10 mm	10	M5	M 4
K- 07 15 17 15	10 mm	25	M5	M 4
K- 07 15 17 16	10 mm	50	M5	M 4
K- 07 15 17 17	12 mm	10	M5	M 6
K- 07 15 17 18	12 mm	25	M5	M 6
K- 07 15 17 19	12 mm	50	M5	M 6
K- 07 15 17 20	16 mm	10	M5	M 6
K- 07 15 17 21	16 mm	25	M5	M 6
K- 07 15 17 22	16 mm	50	M5	M 6
K- 07 15 17 23	20 mm	10	G 1/8"	M 8
K- 07 15 17 24	20 mm	25	G 1/8"	M 8
K- 07 15 17 25	20 mm	50	G 1/8"	M 8
K- 07 15 17 26	25 mm	10	G 1/8"	M 10 x 1.25
K- 07 15 17 27	25 mm	25	G 1/8"	M 10 x 1.25
K- 07 15 17 28	25 mm	50	G 1/8"	M 10 x 1.25