



Modelis
Gliemežvītnes skavas
Papildinājums modelim
Sešstūra skrūves galviņa ar mīnusu
Materiāls
Nerūsējošais tērauds 1.4016

Norādot

Skrūve ir no cinkota un dzeltenī hromēta tērauda.

Produkts

| Apzīmējums | Iespilēšanas diapazons (mm) | Lentes platums mm |
|-------------------|-----------------------------|----------------------|
| ESK 08-12 W2 | 8 - 12 | 9.0 |
| ESK 10-16 W2 | 10 - 16 | 9.0 |
| ESK 12-20 W2 | 12 - 20 | 9.0 |
| ESK 16-25 W2 | 16 - 25 | 9.0 |
| ESK 20-32 W2 | 20 - 32 | 9.0 |
| ESK 25-40 W2 | 25 - 40 | 9.0 |
| ESK 32-50 W2 | 32 - 50 | 9.0 |
| ESK 40-60 W2 | 40 - 60 | 9.0 |
| ESK 50-70 W2 | 50 - 70 | 9.0 |
| ESK 60-80 W2 | 60 - 80 | 9.0 |
| ESK 70-90 W2 | 70 - 90 | 9.0 |
| ESK 80-100 W2 | 80 - 100 | 9.0 |
| ESK 90-110 W2 | 90 - 110 | 9.0 |
| ESK 100-120 W2 | 100 - 120 | 9.0 |
| ESK 110-130 W2 | 110 - 130 | 9.0 |
| ESK 120-140 W2 | 120 - 140 | 9.0 |
| ESK 130-150 W2 | 130 - 150 | 9.0 |
| ESK 12 16-25 W2 | 16 - 25 | 12.0 |
| ESK 12 20-32 W2 | 20 - 32 | 12.0 |
| ESK 12 25-40 W2 | 25 - 40 | 12.0 |
| ESK 12 32-50 W2 | 32 - 50 | 12.0 |
| ESK 12 40-60 W2 | 40 - 60 | 12.0 |
| ESK 12 50-70 W2 | 50 - 70 | 12.0 |
| ESK 12 60-80 W2 | 60 - 80 | 12.0 |
| ESK 12 70-90 W2 | 70 - 90 | 12.0 |
| ESK 12 80-100 W2 | 80 - 100 | 12.0 |
| ESK 12 90-110 W2 | 90 - 110 | 12.0 |
| ESK 12 100-120 W2 | 100 - 120 | 12.0 |
| ESK 12 110-130 W2 | 110 - 130 | 12.0 |