



Izmantošana  
Blīvgredzens TRI skavu iemavām  
Modelis  
Formas blīvgredzens no PTFE  
Standarts  
DIN 32676  
Temperatūras diapazons  
no -200 °C līdz 260 °C  
Materiāls  
PTFE (politetrafluoretilēns)

## Produkts

| Apzīmējums            | DN  | D<br>mm | d<br>mm |
|-----------------------|-----|---------|---------|
| DIRITRI DN10 D34 PT   | 10  | 34.0    | 10.2    |
| DIRITRI DN15 D34 PT   | 15  | 34.0    | 16.2    |
| DIRITRI DN20 D34 PT   | 20  | 34.0    | 20.2    |
| DIRITRI DN25 D50.5 PT | 25  | 50.5    | 26.2    |
| DIRITRI DN32 D50.5 PT | 32  | 50.5    | 32.2    |
| DIRITRI DN40 D50.5 PT | 40  | 50.5    | 38.2    |
| DIRITRI DN50 D64 PT   | 50  | 64.0    | 50.2    |
| DIRITRI DN65 D91 PT   | 65  | 91.0    | 66.2    |
| DIRITRI DN80 D106 PT  | 80  | 106.0   | 81.2    |
| DIRITRI DN100 D119 PT | 100 | 119.0   | 100.2   |
| DIRITRI DN125 D133 PT | 125 | 155.0   | 125.2   |
| DIRITRI DN150 D183 PT | 150 | 183.0   | 150.2   |