



Izmantošana
Blīvgredzens TRI skavu iemavām
Modelis
Formas blīvgredzens no PTFE
Standarts
DIN 32676
Temperatūras diapazons
no -200 °C līdz 260 °C
Materiāls
PTFE (politetrafluoretilēns)

Produkts

| Apzīmējums | DN | D mm | d mm |
|-----------------------|-----|---------|---------|
| DIRITRI DN10 D34 PT | 10 | 34.0 | 10.2 |
| DIRITRI DN15 D34 PT | 15 | 34.0 | 16.2 |
| DIRITRI DN20 D34 PT | 20 | 34.0 | 20.2 |
| DIRITRI DN25 D50.5 PT | 25 | 50.5 | 26.2 |
| DIRITRI DN32 D50.5 PT | 32 | 50.5 | 32.2 |
| DIRITRI DN40 D50.5 PT | 40 | 50.5 | 38.2 |
| DIRITRI DN50 D64 PT | 50 | 64.0 | 50.2 |
| DIRITRI DN65 D91 PT | 65 | 91.0 | 66.2 |
| DIRITRI DN80 D106 PT | 80 | 106.0 | 81.2 |
| DIRITRI DN100 D119 PT | 100 | 119.0 | 100.2 |
| DIRITRI DN125 D133 PT | 125 | 155.0 | 125.2 |
| DIRITRI DN150 D183 PT | 150 | 183.0 | 150.2 |