

K-INLINE-DRG IG WASSER 0 SEKUNDAER

Inline pressure regulators, for water applications



Ekspluatācijas spiediens
maks. 10 bar
Temperatūras diapazons
0 °C to +60 °C
Caurplūde
4000 ml/min with 0.8 bar pressure loss
citas daļas
CR, stainless steel
Korpuss
Nickel-plated brass

Apraksts

This water regulator is designed as a single-acting diaphragm regulator for installation in any water pipe system. It supplies a precise output value regardless of the input pressure. Since the pressure is preset in the factory and cannot be altered, the product is also tamper-proof.
The regulator protects all downstream devices and components in the water pipe by maintaining a required constant pressure and preventing system pressure fluctuations. In combination with a nozzle, it is ideally suited for cooling or cleaning with water spray or mist.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Priekšiestatītais darba spiediens	A mm	B	SW mm
K- 07 25 03 06	G 1/4	1 bar	34.0	51.0 mm	17
K- 07 25 03 07	G 1/4	2 bar	34.0	51.0 mm	17
K- 07 25 03 08	G 1/4	3 bar	34.0	51.0 mm	17
K- 07 25 03 09	G 1/4	4 bar	34.0	51.0 mm	17